



## DATA SHEET

### Solvar D240

#### SPECIFICATIONS

MEASURES	UNITS	MEASURES METHODS	GUARANTEED VALUES	
			MINI	MAXI
Appearance		Visual	Clear and bright	
Saybolt Color		ASTM D156	+30	
Aromatic content	ppm	U.V.		100
Flash Point	°F	ASTM D93	241	
Initial Point	°F	ASTM D86	490	
Final Point	°F	ASTM D86		540
Viscosity at 104°F (40°C)	mm <sup>2</sup> /s	ASTM D445	2.5	3

#### TYPICAL VALUES

MEASURES	UNITS	MEASURES METHODS	TYPICAL VALUES
Density at 59°F	Kg/m <sup>3</sup>	ASTM D4052	817
Benzene content	ppm	ASTM D6229	<1*
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	2.9
Pour point	°F	ASTM D97	-40
Sulfur content	ppm	ASTM D5453	<1
Aniline point at 68°F (20°C)	°F	ASTM D611	183
Vapor pressure at 68°F (20°C)	kPa	Calculated	0.0008

Approval date: 11/08/2012

\*Levels below 1ppm minimum level for detection

CAS No.: 64742-46-7



**DATA SHEET**