



Solvar D 310

SPECIFICATIONS

MEASURES	UNITS	MEASURES METHODS	GUARANTEED VALUES	
			MINI	MAXI
Appearance		Visual	Clear and bright	
Saybolt Color		ASTM D 156	+30	
Aromatic content	ppm	U.V.		200
Flash Point	° F	ASTM D 93	304	
Boiling range - Initial Point	° F	ASTM D 86	563	
Boiling range - Final Point	° F	ASTM D 86		712
Viscosity at 104° F (40° C)	mm ² /s	ASTM D 445	6.6	7.5

TYPICAL VALUES

MEASURES	UNITS	MEASURES METHODS	TYPICAL VALUES
Density at 59 ° F	Kg/m ³	ASTM D 4052	823
Benzene content	ppm	ASTM D 6229	0*
Viscosity at 40°C	mm ² /s	ASTM D 445	7.1
Pour point	° F	ASTM D 97	0
Lbs / Gallon	-	-	6.86
Sulfur content	ppm	ASTM D 5453	<1
Aniline point at 68° F (20° C)	° F	ASTM D 611	216
Vapor pressure at 68° F (20° C)	kPa	Calculated	<0.0001

Approval date: 4/12/2010

*Levels below 1ppm minimum level for detection

CAS No.: 64742-55-8