



## Solvar N 55

### SPECIFICATIONS

MEASURES	UNITS	MEASURES METHODS	GUARANTEED VALUES	
			MINI	MAXI
Appearance		Visual	Clear and bright	
Saybolt Color		ASTM D156	+25	
Aromatic content	ppm	U.V.		10,000
Flash Point	° F	ASTM D 93	342	
Boiling range - Initial Point	° F	ASTM D 86	630	
Boiling range - Final Point	° F	ASTM D 86		708
Viscosity at 104° F (40° C)	mm <sup>2</sup> /s	ASTM D 445	9	11

### TYPICAL VALUES

MEASURES	UNITS	MEASURES METHODS	TYPICAL VALUES
Density at 59 ° F	Kg/m3	ASTM D 4052	867
Benzene content	ppm	ASTM D 6229	0*
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	10
Pour point	° F	ASTM D 97	-35
Lbs / Gallon	-	-	7.22
Sulfur content	ppm	ASTM D 5453	<5
Aniline point at 68° F (20° C)	° F	ASTM D 611	206
Vapor pressure at 68° F (20° C)	kPa	Calculated	<0.13

Approval date: 7/1/2010

\*Levels below 1ppm minimum level for detection

CAS No.: 64742-54-7 / 64742-55-8